# Enregistreur de données de température avec capteur intégré et modem 2G

code: U3120M




L'enregistreur de données est conçu pour enregistrer la température et l'humidité. En cas de dépassement des limites définies, les messages SMS et JSON peuvent être envoyés via une connexion de données GPRS. Il est possible de définir l'envoi régulier de messages JSON à la base de données COMET, l'intervalle d'envoi est réglable.
L'enregistrement est effectué dans une mémoire électronique non volatile. Les données peuvent être transférées sur un PC via USB-C.

L'appareil comprend un **certificat d'étalonnage traçable** avec une traçabilité métrologique déclarée des étalons basé sur les exigences de la norme EN ISO / IEC 17025.

## Données techniques

| | |
|---|---|
| TEMPERATURE SENSOR | |
| Measuring range | -20 to +60 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | 0 to 100 % RH |
| Accuracy | ± 1.8 % RH |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | -90 to +60 °C |
| Accuracy | ±1.5 °C at ambient temperature T <25 °C and RH >30 % |
| Resolution | 0.1 °C |
| GSM MODEM PARAMETERS | |
| Quad-band | 850/900/1800/1900MHz |
| Compliant to GSM | Phase2/2+ |
| GPRS | GPRS mobile station class B |
| Class 4 | 2W @ 850/900MHz |
| Class 1 | 1W @ 1800/1900MHz |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -20 to +60 °C |
| Channels | internal temperature and humidity sensor |
| Memory | 500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode |
| Recording interval to the internal memory | adjustable from 1 second to 24 hours |
| Recording interval to the COMET Cloud | from 5 minutes |
| Interval for measuring and evaluating alarms | adjustable 1 s, 10 s, 1 min |

| | |
|---|---|
| Recording mode | noncyclic - data logging stops after filling the memory<br>cyclic - after filling memory oldest data is overwritten by new |
| Real time clock | year, leap year, month, day, hour, minute, second |
| Power | rechargeable Li-Ion battery A8200, 3.6V/5200mAh |
| Protection class | IP67 electronics; IP30 sensors |
| Dimensions | 61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm |
| Weight (including batteries) | approx. 260 g |
| Warranty | 3 years |